

CERBERUS® XL C-UAS

Multi-Sensor Counter UAS Solution

Cerberus XL C-UAS is a rugged, state of the art integrated system, with high performance, long-range Counter Unmanned Aerial Systems (C-UAS) sensors, proven for rapid deployment in austere environments. It provides unmanned perimeter and border UAS situational awareness and multi-mission security. The fully integrated solution includes radar, EO/IR, and RF detection and mitigation for both ground and air threats, including Group 1 and 2 UAS, with a robust command and control system and AI/ML interface. Cerberus XL C-UAS is sensor and C-UAS effector agnostic.

Provides accurate track data for precise target acquisition. It can easily integrate into existing defense kinetic effector systems, and additional detection and defeat technologies as available. All sensors are integrated into an easy-to-deploy trailer platform, equipped with a control system using the Teledyne FLIR Cameleon interface, optimized for C-UAS, surveillance, and security missions. The Cerberus XL C-UAS addresses the entire UAS kill chain including detect, track, identify, and defeat.

APPLICATIONS

**AIRPORT SECURITY | MILITARY FLIGHT LINE
SECURITY | PORT SECURITY | BORDER
SECURITY | MILITARY FORCE PROTECTION**

FEATURES

MODULARITY

Designed to support a variety of sensors and payloads, the system offers multiple range configurations tailored to mission requirements. Its modular architecture allows for easy customization with pre-integrated sensors and the capability to incorporate new components as needed for specific operational needs.

CONTINUOUS AIR DEFENSE

Maintain uninterrupted air security by detecting and tracking over 500 targets simultaneously with advanced radar and RF technology. Integrated imaging and RF sensors provide real-time detection, tracking, and identification of potential threats, ensuring comprehensive situational awareness and rapid threat response.

INTEGRATED COMMAND & CONTROL

The Teledyne Cameleon C2 client interface offers mapping, track display, camera control, mission recording, and system health monitoring. The NNTC video analytics enhances radar tracks for real-time awareness. An integrated API enables data sharing and command reception, optimizing mission effectiveness, and sensors and effectors control.



RAPIDLY DEPLOYABLE, RUGGED TRAILER PLATFORM

Fast deployment in extreme conditions, the Cerberus XL C-UAS system features a free-standing, fixed mast trailer platform for land, sea, and air missions. All components are managed from a unified control system. It includes a two-axis inclinometer and digital GPS for precise targeting on uneven terrain and operates in GPS/GNSS-denied environments.

MULTI-DOMAIN USE

Versatile across land, air, and marine domains, the system is optimized with full, - distinct C-UAS operational modes. Each mode is tailored to effectively detect, track, identify and engage air threats in its specific environment, ensuring maximum mission adaptability and efficiency.

SOFT KILL CHAIN

A layered countermeasure system using radar and RF for detection, jamming and disruption, and EO/IR for precise tracking and identification. Design for precise target acquisition our C2 moves this data into a single integrated picture and used filtered data to cue kinetic options capability, depending on mission needs.

SPECIFICATIONS

ARCHITECTURE	
Base Platform	Long range, Teledyne FLIR EO/IR, radar, Power/Communication enclosure, multiple mast heights, and tactical trailer platform.
PHYSICAL CHARACTERISTICS	
Weight	~ 4200lbs
Length	175 in. (444.5 cm) including the tongue
Width	87 in. (221 cm)
Height 3m Fixed Mast	• Shipment, w/payloads stored, and mast disassembled: 103 in (262 cm) • Mobilized, w/cameras stored (MS 1200): 152 in (386 cm) • Deployed, w/cameras mounted: 158 in (401 cm) - Other mast options available
Power	24V DC nominal operated system sourced by an onboard 5.5kW battery bank provides both silent and reduced heat signature operation. System charges from a single phase 90-240VAC 50/60Hz grid power source or its onboard AC diesel generator. • US 120VAC 60Hz (Std) • Global 220-240VAC, 50Hz 2220W nominal operating, 3250W max operating (Std Config) 2050W max charging on a 120VAC grid source (2500W 220-240VAC)
RADAR AND EO/IR SENSORS	
Radar Standard	360° quad-radar array air and ground coverage • R20SS-3Ds-XR (Std) • R20-3Ds (Opt)
Standard EO/IR System	HDC-MS 1200/1000 • High Definition (HD) Mid-Wave Infrared (MWIR) • High Definition (HD) Color • Laser Rangefinder (NIR wavelength) • Laser Pointer (NIR wavelength)
Included in Base System	Rugged Cameleon Client laptop Cameleon Tactical V5 and Licenses 1yr Software Assurance 1yr System Warranty
COMMAND & CONTROL	
Cameleon Tactical V5	TDY FLIR's advanced VMS, enhanced with EO/IR video AI and sensor data fusion, displays up to 500 real-time geolocated targets from integrated EO/IR, radar, and RF sensors. Features: - Operator controls like slew-to-cue, automated target tracking with history and alarms - Mapping with POI overlays and zone management - Video archive, playback, and distribution - Alarms - 3rd party C2 interoperability via Cursor-on-Target (CoT) - Scalable client/server architecture - Wireless communication options - CoT/TAK integration for target sharing, field-of-view, and blue-force tracking
Multi-sensor Tracking	Up to 500 Targets. Automatic bi-directional handoff between radar and video AI tracking, sensor blending to improve radar track accuracy based on video AI detection.

POWER AND ENVIRONMENTAL

Power	24V DC nominal system powered by an onboard 5.5kW battery bank for silent operation Charges via single-phase 90-240VAC 50/60Hz grid power or onboard diesel generator US 120VAC 60Hz (Standard) / Global 220-240VAC 50Hz Power consumption: 2220W nominal, 3250W max (Standard configuration) 2050W max charging on 120VAC (2500W on 220-240VAC)
Test	MIL-STD-810H Compliant 502.7 I/II Low Temperature (C1) 505.7 I Solar (A1) 510.7 I/II Sand and dust

COUNTER DRONE TECHNOLOGY

Detect & Defeat	Standard Configuration: (RF) 2.4 GHz / 5.8 GHz / Wi-Fi; Extended Frequency 433 / 868 / 915 MHz / 1.2 GHz / Wi-Fi Existing options for additional RF and Kinetic technologies. Other technologies available upon request
Detection Range	Standard Configuration: Up to 3 km horizontal; 457 m vertical (variable with noise floor & environment)
Defeat Range	Standard Configuration: Up to 1.5 km horizontal; 457 m vertical (variable with noise floor & environment)

DEPLOYMENT

Mast Deploy and System Fully Operational	In less than 30 minutes (Two Person)
US Export Classification	USML VII(c) - Standard Configuration



AMERICAS

7055 Troy Hill Dr. Suite 300
Elkridge, MD 21075 USA

EUROPE

2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom

Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden

MIDDLE EAST

Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit /
Khalifa Park Area
Abu Dhabi, U.A.E.

Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia

ASIA

10 Kallang Avenue #09-10,
Aperia Tower 2
Singapore 339510

The information contained in this page pertains to products that may be subject to the International Traffic in Arms Regulations (ITAR) (22 C.F.R. Sections 120-130) or the Export Administration Regulations (EAR) (15 C.F.R. Sections 730-774) depending upon specifications for the final product; jurisdiction and classification will be provided upon request. ©2024 Teledyne FLIR LLC. All rights reserved.

Revised on 10/11/24
CerberusXL_CUAS_Datasheet-LTR 24-1010